For Commercial Applications

Job Name	Item Designation
Job Location	Contractor
Engineer	Representative
Inlet: P-1/2 P-3/4 CP C	Finish: CH BR PC

For Non Freezing Areas

Woodford Model 26

Backflow ProtectedWall Faucet

The Model 26 is a backflow protected wall faucet designed for use in mild climate areas. The Model 26 is intended for irrigation purposes and is designed to blend in with modern architecture for installation on homes, service stations, churches, motels, drive-in restaurants, etc.

Features:

- EPDM Packing
- · Adjustable brass packing nut
- Standard "O" size valve seat washer
- · Polycarbonate wheel handle and loose tee key

Optional: Metal wheel handle

• 4 inlet options


Specifications:

PATENTED HIGH FLOW DOUBLE CHECK BACKFLOW PREVENTER


- NIDEL® Model 50HF with $3\!\!\!/_4$ inch male hose thread
- ASSE Standard 1052 approved
- Field Testable
- Two Independent Check Valves
- · Drains automatically when hose is removed
- No spray back
- Maximum Working Pressure: 125 p.s.i.
- Maximum Temperature: 120° F

Specify as follows:
Wall faucet shall be a Woodford Model 26 for non-freezing areas with ASSE 1052 approved NIDEL® Model 50HF high flow double check backflow preventer. ¾" hose connection (specify type of inlet). Exterior finish to be Chrome Plated (options: Rough Brass or Polished Chrome). Loose tee key to be furnished with each faucet. Intended for irrigation purposes. Inlet Type _____

Model & Inlet



Optional - Rough Brass (BR) or Polished Chrome (PC) Rough-In Dimensions - Typical





WOODFORD MANUFACTURING COMPANY LLC.

2121 WAYNOKA ROAD COLORADO SPRINGS, CO 80915 Phone (800) 621-6032 Website: www.woodfordmfg.com Email: sales @woodfordmfg.com