For Commercial Applications

Job Name	Item Designation
Job Location	Contractor
Engineer	Representative
nlet: 3/4" Female Pipe Thread Only	Finish: CH BR PB

For Non Freezing Areas

WoodfordModel 79

Backflow Protected 360° Close Coupled Inlet Trimline Wall Hydrant

The Model 79 is a Backflow protected wall hydrant intended for irrigation purposes and is designed for use in mild climate areas or within temperature controlled buildings. The Model 79 is only 2-5/8" deep and fits within a 2 x 4 stud wall.

Features:

- · Red Brass head & valve body
- · Hemispherical valve seat
- Hardened stainless steel operating stem
- EPDM Packing
- · Adjustable brass packing nut
- Loose Tee Key operation
- 3/4" female pipe thread inlet swivels 360° to any position


Specifications:

PATENTED HIGH FLOW DOUBLE CHECK BACKFLOW PREVENTER

- NIDEL® Model 50HF with ¾ inch male hose thread
- · ASSE Standard 1052 approved
- Field Testable
- Two Independent Check Valves
- Drains automatically when hose is removed
- No spray back
- Maximum Working Pressure: 125 p.s.i.
- Maximum Temperature: 120° F

Specify as follows:


Wall hydrant shall be a Woodford Model 79 for non-freezing areas with ASSE 1052 approved NIDEL® Model 50HF high flow double check backflow preventer. ¾" hose connection inlet and outlet. 360° inlet orientation. Hardened stainless steel operating stem. Packing nut secured with lock nut. Permanent type valve body with large hemispherical seating surface. Exterior finish to be Chrome Plated (options: Rough Brass or Polished Brass). Intended for irrigation purposes. Loose tee key to be furnished with each hydrant.



Exterior Finish:

Standard - Chrome (CH)
Optional - Rough Brass (BR) or Polished Brass (PB)

Rough-In Dimensions





WOODFORD MANUFACTURING COMPANY LLC.

2121 WAYNOKA ROAD COLORADO SPRINGS, CO 80915 Phone (800) 621-6032 Website: www.woodfordmfg.com

Email: sales@woodfordmfg.com

2025 WOODFORD Mfg. Rev. 7/12 Form No. SS79.104